



ELECTRICAL CHARACTERISTICS:
 R25C=10,000 OHMS NOM
 ± 0.1 °C FROM 0C TO 100C (4PT CALIBRATION)
 0.01 °C RESOLUTION

<100mA CURRENT DRAW

MECHANICAL CHARACTERISTICS:
 LEADS:
 #22 AWG PVC CABLE.
 LENGTH=5"

ADHESIVE WALLED HEATSHRINK, LENGTH=1.0"
 QTI P/N: QT01010-001

NOTES:

	INITIAL	DATE
DRAWN	BR	8/17/09
ENG APPR.	<i>Gay Kochauer</i>	08 17, 2009
MAT APPR.	<i>Jim Larson</i>	Aug 17, 2009
Q.A. APPR.	<i>D. J. M.</i>	Aug 18, 2009



2108 CENTURY WAY
 BOISE, ID 83709
 WWW.THERMISTOR.COM

QTI PART NUMBER: **DTU6002-001-N** REV -

SIZE **A** DWG. NO. **DTU6002-001-N.SLDDRW**

SHEET 1 OF 1

DIMENSIONS ARE IN INCHES
 TOLERANCES:
 FRACTIONAL ±1/8
 .X ±0.1
 .XX ±0.02
 .XXX ±0.005

DATE	REVISION	INITIAL
8/17/09	-	BR

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF QUALITY THERMISTOR, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF QUALITY THERMISTOR, INC. IS PROHIBITED.