



ELECTRICAL CHARACTERISTICS:
R25C=10,000 OHMS NOMINAL

<100mA CURRENT DRAW

MECHANICAL CHARACTERISTICS:

LEADS:
BELDEN 1508A SHIELDED, PVC JACKETED CABLE,
#24AWG, 7/32 STRANDED TINNED COPPER,
LENGTH=6' NOM
QTI P/N: QT01002-238

HOUSING:
316 STAINLESS STEEL, POLISHED
0.010" WALL ON 0.125" OD TUBE
QTI P/N: QT01005-303

CONICAL WIRE SPRING STRAIN RELIEF
QTI P/N: QT01021-003

NOTES:

	INITIAL	DATE
DRAWN	BR	6/17/09
ENG APPR.	<i>Jay Kochaew</i>	06 17, 2009
MAT APPR.	<i>Jim Larson</i>	Jun 17, 2009
Q.A. APPR.	<i>Dave & M...</i>	Jun 17, 2009



2108 CENTURY WAY
BOISE, ID 83709
WWW.THERMISTOR.COM

QTI PART NUMBER:

DTU6005-002

REV
B

SIZE DWG. NO.

A DTU6005-002.SLDDRW

6/17/09	B	BR
5/06/09	A	BR
02/02/09	-	BR
DATE	REVISION	INITIAL

DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL ±1/8
.X ±0.1
.XX ±0.02
.XXX ±0.005

SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF QUALITY THERMISTOR, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF QUALITY THERMISTOR, INC. IS PROHIBITED.