



ELECTRICAL CHARACTERISTICS:
 R25C=10,000 OHMS ±5%
 BETA=3435

< 100mA CURRENT DRAW

MECHANICAL CHARACTERISTICS:

LEADS:
 #24 AWG BELDEN CABLE
 7/32 STRANDED, LENGTH=48" NOM
 HI FLEX BLACK JACKET
 QTI P/N: QT01002-238

BELDEN P/N: 1508A

HOUSING:
 FLAT KAPTON TAPE
 QTI P/N: QT01018-048

NOTES:

	INITIAL	DATE
DRAWN	BR	8/06/09
ENG APPR.	<i>Paula Olson</i>	Aug 10, 2009
MAT APPR.	<i>Steve Lange</i>	Aug 07, 2009
Q.A. APPR.	<i>D. J. & M. M.</i>	Aug 10, 2009



2108 CENTURY WAY
 BOISE, ID 83709
 WWW.THERMISTOR.COM

QTI PART NUMBER: **DTU6005-005** REV **-**

SIZE **A** DWG. NO. **DTU6005-005.SLDDRW**

DIMENSIONS ARE IN INCHES
 TOLERANCES:
 FRACTIONAL ±1/8
 .X ±0.1
 .XX ±0.02
 .XXX ±0.005

DATE	REVISION	INITIAL
8/06/09	-	BR

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF QUALITY THERMISTOR, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF QUALITY THERMISTOR, INC. IS PROHIBITED.