



ELECTRICAL CHARACTERISTICS:
 R25C=10,000 OHMS NOMINAL
 ±.1 °C FROM 0C TO 100C (4PT. CALIBRATION)
 0.01 °C RESOLUTION
 <100mA CURRENT DRAW

MECHANICAL CHARACTERISTICS:
 LEADS:
 #24 AWG BELDEN CABLE
 7/32 STRANDED, LENGTH=5' NOM
 HI FLEX, BLACK JACKET
 QTI P/N: QT01002-238

BELDEN P/N: 1508A

 HOUSING:
 NICKEL PLATED #6 RING LUG
 QTI P/N: QT01005-231

NOTES:

	INITIAL	DATE
DRAWN	BR	6/16/09
ENG APPR.	<i>Gay Kochaer</i>	06 17, 2009
MAT APPR.	<i>Don Lauer</i>	Jun 17, 2009
Q.A. APPR.	<i>David & Mar</i>	Jun 16, 2009

QUALITY THERMISTOR, INC.
 2108 CENTURY WAY
 BOISE, ID 83709
 WWW.THERMISTOR.COM

QTI PART NUMBER: DTU6009-003-N
 REV -

SIZE DWG. NO.
A DTU6009-003-N.SLDDRW

DIMENSIONS ARE IN INCHES
 TOLERANCES:
 FRACTIONAL ±1/8
 .X ±0.1
 .XX ±0.02
 .XXX ±0.005

6/16/09	-	BR
DATE	REVISION	INITIAL

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF QUALITY THERMISTOR, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF QUALITY THERMISTOR, INC. IS PROHIBITED.