



STANDARD USB PACKAGE

MOLDED STRAIN RELIEF
QT01011-047

ELECTRICAL CHARACTERISTICS:
R25C=10,000 OHMS NOMINAL
<100mA CURRENT DRAW

MECHANICAL CHARACTERISTICS:
LEADS:
28 AWG PVC COILED CABLE, 13.0" RETRACTED,
60.0" EXTENDED.
QTI P/N: QT01002-282

HOUSING:
316 STAINLESS STEEL W/MACHINED PLASTIC
HANDLE
QTI P/N: QT01005-295

CONNECTOR:
PRECISION USB, OVER MOLDED
QTI P/N: QT01016-021

NOTES:

	INITIAL	DATE
DRAWN	DM	10/28/08
ENG APPR.	<i>Greg Kochauer</i>	06 30, 2009
MAT APPR.	<i>Jim Lange</i>	Jun 30, 2009
Q.A. APPR.	<i>Dick & Ann</i>	Jul 01, 2009

2108 CENTURY WAY
BOISE, ID 83709
WWW.THERMISTOR.COM

QTI PART NUMBER: DTU6028-001 REV C

SIZE DWG. NO.
A DTU6028-001.SLDDRW

DATE	REVISION	INITIAL
06/29/09	C	BR
02/10/09	B	BR
12/01/08	A	BR
10/29/08	-	DM

DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL ±1/8
.X ±0.1
.XX ±0.02
.XXX ±0.005

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF QUALITY THERMISTOR, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF QUALITY THERMISTOR, INC. IS PROHIBITED.