



ISO VIEW
NOT TO SCALE



ELECTRICAL CHARACTERISTICS:
R25C=10K OHMS +/-0.1C (0C-70C)
RT CURVE Z, NTC=-4.4%/C @ 25C

OPERATING TEMPERATURE: -50C TO 100C
STORAGE TEMPERATURE: -55C TO 125C

MECHANICAL CHARACTERISTICS:
LEADS:
#38 AWG CONSTANTAN, SINGLE
POLYNYLON INSULATION, OR EQUIVALENT
QTI P/N: QT01015-043

HOUSING:
POLYIMIDE TUBE, EPOXY FILLED
QTI P/N: QT01010-092

CONNECTOR:

NOTES:

Ø .020 MAX

	INITIAL	DATE
DRAWN	<i>Bush Olson</i>	Apr 29, 2009
ENG APPR.	<i>Gay Kochavaer</i>	04 29, 2009
MAT APPR.	<i>Don Larson</i>	Apr 29, 2009
Q.A. APPR.	<i>D. & M.</i>	05/05/09



Quality Thermistor, Inc. 2108 CENTURY WAY
BOISE, ID 83709

QTI PART NUMBER: QTUT-14D3	REV -
--------------------------------------	----------

SIZE A	DWG. NO. QTUT-14D3
------------------	-----------------------

SCALE: 5:1	APPROVED FORM: QT05006-168 REV.-	SHEET 1 OF 1
------------	-------------------------------------	--------------

DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL ±1/8
.X ±0.1
.XX ±0.02
.XXX ±0.005

4/23/09	-	BC
DATE	REVISION	INITIAL

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
QUALITY THERMISTOR, INC. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
QUALITY THERMISTOR, INC. IS PROHIBITED.